

# Ball valve unit
# VZBA-A-11/4-GG-63-T-22-F0405-V4V4T-PB60

Part number: 8191817





## Data sheet

| Feature | Value |
|---|---|
| Design | 2-way ball valve<br>Quarter turn actuator |
| Type of actuation | Pneumatic |
| Sealing principle | Soft |
| Mounting position | Any |
| Type of mounting | Inline installation |
| Connection Process valve | Rp1 1/4 |
| Switching position indicator | Slot direction = flow direction |
| Flange hole pattern | F0405 |
| Nominal size DN | 32 |
| Valve function | 2/2 |
| Flow direction | Reversible |
| Operating pressure | 0.55 MPa...0.8 MPa<br>5.5 bar...8 bar<br>79.75 psi...116 psi |
| Nominal pressure PN | 63 |
| Breakaway torque at differential pressure, nominal pressure, process valve PN | 24 Nm |
| Based on standard | DIN 3202-M3<br>EN 10226-1<br>ISO 5211 |
| Medium | Compressed air to ISO 8573-1:2010 [-:-:-]<br>Inert gases<br>Water – no steam<br>Neutral fluids<br>Other media on request |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| Media temperature | -10 °C...200 °C |
| Flow rate Kv | 105 m³/h |
| Max. surface temperature assembly | +105°C...+280°C<br>T4...T2 |
| explosion group assembly | IIC, IIIC |

| Feature | Value |
|---|---|
| Note on materials | RoHS compliant |
| LABS (PWIS) conformity | VDMA24364 zone III |
| Material housing | High-alloy stainless steel |
| Material number housing | 1,4408 |
| Material seat seal | PTFE |
| Material seals | PTFE-reinforced |
| Material ball | High-alloy stainless steel |
| Material number ball | 1,4408 |
| Material shaft | High-alloy stainless steel |
| Material number shaft | 1,4401 |
| Product weight | 5540 g |
| Explosion protection | Zone 1 (ATEX)<br>Zone 2 (ATEX)<br>Zone 21 (ATEX)<br>Zone 22 (ATEX) |
| Explosion ambient temperature | -10°C <= Ta <= +80°C |
| Corrosion resistance class CRC | 1 - Low corrosion stress |