

Ball screw axis
ELGD-BS-KF-60-400-0H-10P

Part number: 8192263





Data sheet

Feature	Value
Working stroke	400 mm
Size	60
Stroke reserve	0 mm
Ball screw reversing backlash	±0.02 mm
Spindle diameter	12 mm
Spindle pitch	10 mm/U
Mounting position	Any
Guide	Recirculating ball bearing guide
Design	Electromechanical linear axis With ball screw
Type of motor	Stepper motor Servo motor
Spindle type	Ball screw
Functional principle of measuring system	Incremental
Position detection	For inductive sensors
Max. acceleration	15 m/s²
Max. rotational speed	5143 rpm
Max. speed	0.86 m/s
Repetition accuracy	±0.01 mm
Duty cycle	100%
LABS (PWIS) conformity	VDMA24364-C1-L
Suitability for the production of Li-ion batteries	Suitable for battery production with reduced Cu/Zn/Ni values (F1a)
Cleanroom suitability, measured according to ISO 14644-14	Class 4 according to ISO 14644-1 (with vacuum extraction) Class 7 according to ISO 14644-1
Storage temperature	-20 °C...60 °C
Degree of protection	IP40
Ambient temperature	0 °C...60 °C
Impact energy in end positions	0.001 J
Note on the impact energy in the end positions	At maximum homing speed of 0.01 m/s
2nd moment of area Iy	508600 mm⁴
2nd moment of area Iz	685700 mm⁴
Idle torque at vmax	0.14 Nm

Feature	Value
Idle torque at vmin	0.047 Nm
Max. force Fy	2200 N
Max. force Fz	2200 N
Max. force Fy total axis	930 N
Max. force Fz total axis	1300 N
Fy at theoretical life value of 100 km (only guide consideration)	9208 N
Fz at theoretical life value of 100 km (only guide consideration)	9208 N
Max. moment Mx	37 Nm
Max. moment My	15 Nm
Max. moment Mz	15 Nm
Max. moment Mx total axis	31 Nm
Max. moment My total axis	34 Nm
Max. moment Mz total axis	26 Nm
Mx at theoretical life value of 100 km (only guide consideration)	157 Nm
My at theoretical life value of 100 km (only guide consideration)	60 Nm
Mz at theoretical life value of 100 km (only guide consideration)	60 Nm
Distance between slide surface and guide centre	60 mm
Max. radial force at drive shaft	230 N
Max. feed force Fx	1550 N
Torsional mass moment of inertia It	52300 mm⁴
Mass moment of inertia JH per metre of stroke	0.15716 kgcm²
Mass moment of inertia JL per kg of working load	0.02533 kgcm²
Mass moment of inertia JO	0.0635 kgcm²
Feed constant	10 mm/U
Reference service life	5000 km
Maintenance interval	Lifetime lubrication
Moving mass	535 g
Product weight	3934 g
Basic weight for 0 mm stroke	1774 g
Additional weight per 10 mm stroke	54 g
Dynamic deflection (moving load)	0.05% of the axis length, max. 0.5 mm
Static deflection (load in standstill)	0.1% of the axis length
Interface code, actuator	T42
Material end cap	Aluminium gravity die-cast, painted
Material profile	Anodised wrought aluminium alloy
Note on materials	RoHS compliant
Material cover tape	High-alloy stainless steel
Material drive cover	Aluminium gravity die-cast, painted
Material guide slide	Steel
Material guide rail	Steel
Material slide	Wrought aluminium alloy
Material ball screw nut	Steel
Material spindle	Steel