Push-in L-fitting
NPQM-L-G18-Q8-P10-G2

Part number: 8226851



Data sheet

Feature	Value
Size	Standard
Nominal size	5.5 mm
Tubing insertion depth	17.2 mm
Type of seal on screwed plug	Sealing ring
Design	L-shape Push-pull principle
Size of pack	10
Operating pressure complete temperature range	-0.095 MPa...1.6 MPa -0.95 bar...16 bar -13.775 psi...232 psi
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Note on operating and pilot medium	Lubricated operation possible
Corrosion resistance class CRC	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	-20 °C...70 °C
Nominal torque	6 Nm
Tolerance for nominal tightening torque	±20%
Product weight	22 g
Type of mounting	External hex SW13
Pneumatic connection, port 1	Male thread G1/8
Pneumatic connection, port 2	For tubing outside diameter of 8 mm
Material screwed plug	Nickel-plated brass
Note on materials	RoHS compliant
Material housing	Brass, nickel-plated
Material thread seal	NBR
Material release ring	Nickel-plated brass
Material o-ring	NBR
Material tubing seal	NBR
Material tubing clamp component	High-alloy stainless steel