
# Service unit combination MSB6-3/8:I2:I4

Part number: 8233037






## Data sheet

| Feature | Value |
|---|---|
| Size | 6 |
| Series | MS |
| Mounting position | Vertical +/-5° |
| Condensate drain | Fully automatic |
| Design | Fibre filter |
| Max. condensate volume | 38 ml |
| Bowl guard | Plastic bowl guard |
| Operating pressure | 0.2 MPa...1.2 MPa<br>2 bar...12 bar<br>29 psi...174 psi |
| Max. standard flow rate | 900 l/min |
| Operating medium | Compressed air to ISO 8573-1:2010 [6:-:4]<br>Inert gas |
| Corrosion resistance class CRC | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Storage temperature | -10 °C...60 °C |
| Air purity class at output | Compressed air to ISO 8573-1:2010:[5:-:3] |
| Media temperature | -10 °C...60 °C |
| Ambient temperature | -10 °C...60 °C |
| Product weight | 1240 g |
| Type of mounting | With accessories |
| Pneumatic connection, port 1 | G3/8 |
| Pneumatic connection, port 2 | G3/8 |
| Material seals | NBR |
| Material filter | Borosilicate fibre |
| Material housing | Die-cast aluminium |
| Material bowl | Makrolon® |