Cover plate
VABB-L3-10

Part number: 8251747



Data sheet

Feature	Value
Grid dimension	10.5 mm
Valve size	10 mm
Size of pack	1
Operating pressure	-0.09 MPa...1 MPa -0.9 bar...10 bar
Suitability for vacuum	Yes
Approval	RCM c UL us - Recognised (Oil)
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (in which case lubricated operation will always be required)
Corrosion resistance class CRC	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Suitability for the production of Li-ion batteries	Suitable for battery production with reduced Cu/Zn/Ni values (F1a)
Storage temperature	-20 °C...60 °C
Suitable for use with food	NSF H1
Media temperature	-10 °C...60 °C
Relative air humidity	5 - 95%
Ambient temperature	-10 °C...60 °C
Max. tightening torque	0.36 Nm
Nominal torque	0.3 Nm
Tolerance for nominal tightening torque	±20%
Product weight	17 g
Type of mounting	Via through-hole for M2 screw
Note on materials	RoHS compliant
Material cover plate	Reinforced PA
Material seals	HNBR
Material screws	Stainless steel